

A	Dept	Qty
	DC	1
	ED	1
	IE	1
	ISO	1
	PD	1
B	R&D	1
	SD	1
	QA	1
	QC	1
	QE	1

Notes:

Specifications:

1. Contact Resistance: 100mΩ Max.
2. Insulation Resistance: 1000MΩ Min.
3. Dielectric Withstanding Voltage: 500V AC(rms)
For 1 Minute.
4. Current Rating:25mA.
5. Voltage Rating:24V DC rms.
6. Temperature: -25°C~+70°C.
7. Operating Life: 2000 cycle min.

Specifications:

1. Contact Resistance: 100mΩ Max.
2. Insulation Resistance: 1000MΩ Min.
3. Dielectric Withstanding Voltage: 500V AC(rms)
For 1 Minute.
4. Current Rating: 25mA.
5. Voltage Rating: 24V DC rms.
6. Temperature: -25°C~+70°C.
7. Operating Life: 2000 cycle min.

1. Contact Material: Copper Alloy.
2. Contact Plating: Gold Plating Over Nickel.
3. Insulator Material: High temperature 260°C,UL 94V-0.

DS1040-01 - X X X X X

Packing type
B: Tube
T: Tray
R: Tape & reel

Acuator color
W: White

Housing color
B: Black

Mounting type
V: V/T type
S: SMT type

No. of contacts
2 3 4 5 6 7
8 9 10 11 12



(Series Image-Reference Only)

 晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD