

1N5820 THRU 1N5822

Features

- Low Switching Noise
- Low Forward Voltage Drop
- High Current Capability
- High Surge Current Capability

**3 Amp Schottky
Barrier Rectifier
20 - 40 Volts**

Maximum Ratings

- Operating Temperature: -55°C to +125°C
- Storage Temperature: -55°C to +125°C
- Maximum Thermal Resistance; 28 °C/W Junction To Ambient


Catalog Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
1N5820	---	20V	14V	20V
1N5821	---	30V	21V	30V
1N5822	---	40V	28V	40V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I _{F(AV)}	3.0A	T _A = 85°C
Peak Forward Surge Current	FSM	80A	8.3ms, half sine
Maximum Instantaneous Forward Voltage 1N5820 1N5821 1N5822	V _F	.475V .500V .525V	I _{FM} = 3.0A; T _J = 25°C*
Maximum DC Reverse Current At Rated DC Blocking Voltage	R	2.0mA 20mA	T _J = 25°C T _J = 100°C
Typical Junction Capacitance	C _J	200pF	Measured at 1.0MHz, V _R =4.0V

*Pulse test: Pulse width 300 μsec, Duty cycle 1%

DO-201AD



DIMENSIONS					
DIM.	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	---	.370	---	9.50	
B	---	.250	---	6.40	
C	.048	.052	1.20	1.30	
D	1.000	---	25.40	---	

1N5820 thru 1N5822

Figure 1
Typical Forward Characteristics




Figure 2
Forward Derating Curve






Figure 3
Junction Capacitance




1N5820 thru 1N5822

Figure 4
Typical Reverse Characteristics



Instantaneous Reverse Leakage Current - MicroAmperes versus
Percent Of Rated Peak Reverse Voltage - Volts

Figure 5
Maximum Non-Repetitive Forward Surge Current



Peak Forward Surge Current - Amperes versus
Number Of Cycles At 60Hz - Cycles