


Femle Terminal




T-DS1073- S C 6 0 0 ⑥

Contact Plating
6: Tin


Female Terminal

Wire Range		O.D of Wire
Section area mm ²	AWG#	mm
0.33~0.83	22~18	1.7~3.0

Femle Housing





N=No. of contacts




I-DS1073-S C W 0 X ⑥

No. of contact
02~13


V/T Type



Right Angle



N=No. of contacts



NOTES:

1. MAIN SPECIFICATIONS

- . Housing material: NYLON 66
- . Wire range: AWG#22~#18
- . Rated voltage: 250V
- . Rated current: 7A
- . Contact resistance: $\leq 30\text{m}\Omega$
- . Insulation resistance: $\geq 1000\text{M}\Omega$
- . Withstanding voltage: 1000V, AC 1 minute
- . Temperature range: $-25 \sim +85^{\circ}\text{C}$
- . Recommend PC board thickness: 1.6mm

2. PRODUCT NUMBER CODE:

DS1073 - X X X X X

Contact Plating
6: Tin
8: Full gold flashHousing Color
W: WhiteMounting type
R: Right Angle
V: V/T typeConnector type
M: MaleNo. of contact
2 to 13

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	± 0.60	X.	$\pm 5^{\circ}$
.X	± 0.38	.X	$\pm 3^{\circ}$
.XX	± 0.25	.XX	$\pm 2^{\circ}$
DRAWING TYPE		CUSTOMER	
SCALE		1:1	SHEET 1 OF 1
DRAWING NO.		C-DS1073-XXXXXX-C	

PROJECTION	UNIT	TITLE
	mm	P.C.B CONNECTOR 3.96mm VH
SHEET SIZE	A4	SERIES
		DS1073

晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD