

Standard Ratings

Cap.(μ F)	V(Code) Item Code	6.3 (0J)				10 (1A)			
		Case size ϕ D \times L (mm)	Impedance (Ω) MAX.		Rated ripple (mA rms) 105°C / 100kHz	Case size ϕ D \times L (mm)	Impedance (Ω) MAX.		Rated ripple (mA rms) 105°C / 100kHz
			20°C / 100kHz	-10°C / 100kHz			20°C / 100kHz	-10°C / 100kHz	
22	220	5 \times 11	0.60	1.20	180	5 \times 11 ▲ 4 \times 7	0.60 2.00	1.20 5.00	180 65
27	270	4 \times 7	2.00	5.00	65				
33	330	5 \times 11 ▲ 5 \times 7	0.60 0.95	1.20 2.40	180 120	5 \times 11 ▲ 5 \times 7	0.60 0.95	1.20 2.40	180 120
39	390					5 \times 7	0.95	2.40	120
47	470	5 \times 11 ▲ 5 \times 7	0.60 0.95	1.20 2.40	180 120	5 \times 11 ▲ 4 \times 11	0.60 1.30	1.20 2.60	180 120
56	560	5 \times 7	0.95	2.40	120				
68	680	4 \times 11	1.30	2.60	120				
82	820					5 \times 11 ▲ 6.3 \times 7	0.60 0.45	1.20 1.20	180 200
100	101	5 \times 11	0.60	1.20	180	5 \times 11 ▲ 5 \times 15	0.60 0.50	1.20 1.00	180 235
120	121	6.3 \times 7	0.45	1.20	200				
150	151	6.3 \times 11 ▲ 5 \times 15	0.25 0.50	0.50 1.00	290 235	6.3 \times 11	0.25	0.50	290
180	181					6.3 \times 11	0.25	0.50	290
220	221	6.3 \times 11	0.25	0.50	290	6.3 \times 11 ▲ 6.3 \times 15	0.25 0.23	0.50 0.46	290 430
330	331	6.3 \times 11 ▲ 6.3 \times 15	0.25 0.23	0.50 0.46	290 430	8 \times 11.5	0.117	0.234	555
470	471	8 \times 11.5	0.117	0.234	555	8 \times 11.5	0.117	0.234	555
560	561	8 \times 11.5	0.117	0.234	555				
680	681	10 \times 12.5	0.090	0.180	755	10 \times 12.5 ▲ 8 \times 15	0.090 0.085	0.180 0.170	760 730
820	821	8 \times 15 ▲ 10 \times 12.5	0.085 0.090	0.170 0.180	730 755				
1000	102	10 \times 12.5	0.090	0.180	755	10 \times 16 ▲ 8 \times 20	0.068 0.065	0.136 0.130	1050 995
1200	122	8 \times 20 ▲ 10 \times 16	0.065 0.068	0.130 0.136	995 1050	10 \times 20	0.052	0.104	1220
1500	152	10 \times 20	0.052	0.104	1220	10 \times 20 ▲ 10 \times 25	0.052 0.045	0.104 0.090	1220 1440
2200	222	12.5 \times 20 ▲ 10 \times 25	0.038 0.045	0.076 0.090	1655 1440	12.5 \times 20 ▲ 10 \times 31.5	0.038 0.035	0.076 0.070	1655 1815
2700	272	10 \times 31.5	0.035	0.070	1815	12.5 \times 25	0.030	0.060	1945
3300	332	12.5 \times 20	0.038	0.076	1655	12.5 \times 25 ▲ 12.5 \times 31.5	0.030 0.025	0.060 0.050	1950 2310
3900	392	12.5 \times 25	0.030	0.060	1945	12.5 \times 35.5 ▲ 16 \times 20	0.022 0.029	0.044 0.058	2510 2210
4700	472	16 \times 25 ▲ 12.5 \times 31.5	0.022 0.025	0.044 0.050	2555 2310	16 \times 25	0.022	0.044	2555
5600	562	12.5 \times 35.5 ▲ 16 \times 20	0.022 0.029	0.044 0.058	2510 2210	16 \times 25 ▲ 18 \times 20	0.022 0.028	0.044 0.056	2560 2490
6800	682	16 \times 25 ▲ 18 \times 20	0.022 0.028	0.044 0.056	2560 2490	16 \times 31.5 ▲ 18 \times 25	0.018 0.020	0.036 0.040	3010 2740
8200	822	16 \times 31.5	0.018	0.036	3010	16 \times 35.5 ▲ 18 \times 31.5	0.016 0.016	0.032 0.032	3150 3635
10000	103	16 \times 31.5 ▲ 18 \times 25	0.016 0.020	0.032 0.040	3150 2740	18 \times 35.5	0.015	0.030	3680
12000	123	18 \times 31.5	0.016	0.032	3635				
15000	153	18 \times 35.5	0.015	0.030	3680	18 \times 40	0.014	0.028	3800

▲ : In this case, [6] will be put at 12th digit of type numbering system.

Standard Ratings

Cap. (μF)	V(Code)	Item Code	16 (1C)				25 (1E)			
			Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms) 105°C / 100kHz	Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms) 105°C / 100kHz
				20°C / 100kHz	-10°C / 100kHz			20°C / 100kHz	-10°C / 100kHz	
4.7	4R7					5 × 11	0.60	1.20	180	
10	100	5 × 11	0.60	1.20	180	5 × 11 ▲ 4 × 7	0.60 2.00	1.20 5.00	180 65	
15	150	4 × 7	2.00	5.00	65					
22	220	5 × 11 ▲ 5 × 7	0.60 0.95	1.20 2.40	180 120	5 × 11 ▲ 5 × 7	0.60 0.95	1.20 2.40	180 120	
27	270	5 × 7	0.95	2.40	120	4 × 11	1.30	2.60	120	
33	330	5 × 11 ▲ 6.3 × 7	0.60 0.45	1.20 1.20	180 200	5 × 11	0.60	1.20	180	
39	390	4 × 11	1.30	2.60	120	5 × 11 ▲ 6.3 × 7	0.60 0.45	1.20 1.20	180 200	
47	470	5 × 11	0.60	1.20	180	5 × 11	0.60	1.20	180	
56	560	5 × 11 ▲ 6.3 × 7	0.60 0.45	1.20 1.20	180 200	5 × 15	0.50	1.00	235	
82	820	5 × 15	0.50	1.00	235	6.3 × 11	0.25	0.50	290	
100	101	6.3 × 11	0.25	0.50	290	6.3 × 11	0.25	0.50	290	
120	121	6.3 × 11	0.25	0.50	290	6.3 × 15	0.23	0.46	430	
150	151	6.3 × 11	0.25	0.50	290	8 × 11.5	0.117	0.234	555	
180	181	6.3 × 15	0.23	0.46	430					
220	221	8 × 11.5	0.117	0.234	555	8 × 11.5	0.117	0.234	555	
330	331	8 × 11.5	0.117	0.234	555	10 × 12.5 ▲ 8 × 15	0.090 0.085	0.180 0.170	760 730	
470	471	10 × 12.5 ▲ 8 × 15	0.090 0.085	0.180 0.170	760 730	10 × 16 ▲ 8 × 20	0.068 0.065	0.136 0.130	1050 995	
560	561					10 × 20	0.052	0.104	1220	
680	681	10 × 16 ▲ 8 × 20	0.068 0.065	0.136 0.130	1050 995	10 × 20	0.052	0.104	1220	
820	821	10 × 20	0.052	0.104	1220	10 × 25	0.045	0.090	1440	
1000	102	10 × 20	0.052	0.104	1220	12.5 × 20 ▲ 10 × 31.5	0.038 0.035	0.076 0.070	1660 1815	
1200	122	10 × 25	0.045	0.090	1440					
1500	152	12.5 × 20 ▲ 10 × 31.5	0.038 0.035	0.076 0.070	1655 1815	16 × 25 ▲ 12.5 × 25	0.022 0.030	0.044 0.060	2555 1950	
1800	182					12.5 × 31.5 ▲ 16 × 20	0.025 0.029	0.050 0.058	2310 2210	
2200	222	12.5 × 25	0.030	0.060	1945	16 × 25 ▲ 18 × 20 ※ 12.5 × 35.5	0.022 0.028 0.022	0.044 0.056 0.044	2555 2490 2510	
2700	272	12.5 × 31.5 ▲ 16 × 20	0.025 0.029	0.050 0.058	2310 2210	16 × 25	0.022	0.044	2555	
3300	332	16 × 25 ▲ 12.5 × 35.5	0.022 0.022	0.044 0.044	2555 2510	16 × 31.5 ▲ 18 × 25	0.018 0.020	0.036 0.040	3010 2740	
3900	392	16 × 25 ▲ 18 × 20	0.022 0.028	0.044 0.056	2560 2490	16 × 35.5 ▲ 18 × 31.5	0.016 0.016	0.032 0.032	3150 3635	
4700	472	16 × 31.5 ▲ 18 × 25	0.018 0.020	0.036 0.040	3010 2740	18 × 35.5	0.015	0.030	3680	
5600	562	16 × 35.5 ▲ 18 × 31.5	0.016 0.016	0.032 0.032	3150 3635					
6800	682	18 × 35.5	0.015	0.030	3680	18 × 40	0.014	0.028	3800	
8200	822	18 × 35.5	0.015	0.030	3680					
10000	103	18 × 40	0.014	0.028	3800					

▲ : In this case, [6] will be put at 12th digit of type numbering system.
 ※ : In this case, [3] will be put at 12th digit of type numbering system.

Standard Ratings

Cap.(μ F)	V(Code)	Item Code	35 (1V)				50 (1H)			
			Case size ϕ D \times L (mm)	Impedance (Ω) MAX.		Rated ripple (mA rms) 105°C / 100kHz	Case size ϕ D \times L (mm)	Impedance (Ω) MAX.		Rated ripple (mA rms) 105°C / 100kHz
				20°C / 100kHz	-10°C / 100kHz			20°C / 100kHz	-10°C / 100kHz	
0.47	R47									
1	010					5 \times 11	5.00	10.0		25
2.2	2R2					5 \times 11	3.50	7.00		40
3.3	3R3					5 \times 11	3.00	6.00		55
4.7	4R7		5 \times 11	0.60	1.20	180	5 \times 11	2.30	4.60	90
6.8	6R8		4 \times 7	2.00	5.00	65				
10	100		5 \times 11 ▲ 5 \times 7	0.60 0.95	1.20 2.40	180 120	5 \times 11 ▲ 4 \times 11	1.40 2.50	2.80 5.00	120 90
12	120		5 \times 7	0.95	2.40	120				
18	180		4 \times 11	1.30	2.60	120	5 \times 11	1.30	2.60	155
22	220		5 \times 11	0.60	1.20	180	5 \times 11	1.20	2.40	170
27	270		5 \times 11 ▲ 6.3 \times 7	0.60 0.45	1.20 1.20	180 200	5 \times 15	0.90	1.80	215
33	330		5 \times 11	0.60	1.20	180	6.3 \times 11	0.43	0.86	300
39	390		5 \times 15	0.50	1.00	235				
47	470		6.3 \times 11	0.25	0.50	290	6.3 \times 11	0.43	0.86	300
56	560		6.3 \times 11	0.25	0.50	290	6.3 \times 15	0.40	0.80	360
82	820		6.3 \times 15	0.23	0.46	430	8 \times 11.5	0.234	0.468	485
100	101		8 \times 11.5	0.117	0.234	555	8 \times 11.5	0.234	0.468	485
120	121						8 \times 15 ▲ 10 \times 12.5	0.155 0.162	0.310 0.324	635 620
150	151		8 \times 11.5	0.117	0.234	555	10 \times 12.5	0.162	0.324	615
180	181						8 \times 20 ▲ 10 \times 16	0.120 0.119	0.240 0.238	860 850
220	221		10 \times 12.5 ▲ 8 \times 15	0.090 0.085	0.180 0.170	760 730	10 \times 16 ▲ 10 \times 20	0.119 0.090	0.238 0.180	850 1030
270	271						10 \times 25	0.082	0.164	1200
330	331		10 \times 16 ▲ 8 \times 20	0.068 0.065	0.136 0.130	1050 995	10 \times 20 ▲ 10 \times 31.5	0.090 0.060	0.180 0.120	1030 1610
390	391		10 \times 20	0.052	0.104	1220	12.5 \times 20	0.063	0.126	1480
470	471		10 \times 20	0.052	0.104	1220	12.5 \times 20	0.060	0.120	1500
560	561		10 \times 25	0.045	0.090	1440	12.5 \times 25	0.050	0.100	1832
680	681		12.5 \times 20 ▲ 10 \times 31.5	0.038 0.035	0.076 0.070	1660 1815	12.5 \times 25 ▲ 16 \times 20	0.050 0.048	0.100 0.096	1840 1840
820	821						12.5 \times 35.5 ▲ 18 \times 20	0.034 0.042	0.068 0.084	2290 2420
1000	102		12.5 \times 25	0.030	0.060	1950	16 \times 25	0.034	0.068	2235
1200	122		12.5 \times 31.5 ▲ 16 \times 20	0.025 0.029	0.050 0.058	2310 2210	16 \times 31.5 ▲ 18 \times 25	0.028 0.029	0.056 0.058	2700 2610
1500	152		16 \times 25 ▲ 12.5 \times 35.5	0.022 0.022	0.044 0.044	2555 2510	16 \times 31.5 ▲ 16 \times 35.5	0.028 0.025	0.056 0.050	2700 2790
1800	182		16 \times 25 ▲ 18 \times 20	0.022 0.028	0.044 0.056	2555 2490	18 \times 31.5	0.025	0.050	3000
2200	222		16 \times 31.5 ▲ 18 \times 25	0.018 0.020	0.036 0.040	3010 2740	18 \times 35.5	0.023	0.046	3100
2700	272		16 \times 35.5 ▲ 18 \times 31.5	0.016 0.016	0.032 0.032	3150 3635				
3300	332		18 \times 35.5	0.015	0.030	3680				
4700	472		18 \times 40	0.014	0.028	3800				

▲ : In this case, [6] will be put at 12th digit of type numbering system.

ALUMINUM ELECTROLYTIC CAPACITORS

Standard Ratings

V(Code)		63 (1J)				100 (2A)							
Cap.(μF)	Code	Item	Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms) 105°C / 100kHz	Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms) 105°C / 100kHz			
				20°C / 100kHz	-10°C / 100kHz			20°C / 100kHz	-10°C / 100kHz				
0.47	R47						5 × 11	43.0	86.0	20			
1	010						5 × 11	20.0	40.0	30			
2.2	2R2						5 × 11	9.80	19.6	44			
3.3	3R3						5 × 11	6.60	13.2	58			
4.7	4R7		5 × 11	4.70	9.40	68	5 × 11	4.60	9.20	74			
6.8	6R8		5 × 11	2.50	5.00	95	5 × 11	3.50	7.00	95			
		▲ 4 × 11	3.50	7.00	80								
10	100		5 × 11	2.10	4.20	110	6.3 × 11	1.80	3.60	130			
12	120		5 × 11	2.00	4.00	145							
15	150		6.3 × 11	1.20	2.40	160	8 × 11.5	0.83	1.66	180			
18	180		5 × 15	1.30	2.60	200	6.3 × 15	0.80	1.60	200			
22	220		6.3 × 11	0.71	1.42	250	8 × 11.5	0.68	1.36	230			
33	330		6.3 × 11	0.71	1.42	250	10 × 12.5	0.46	0.92	320			
		▲ 8 × 15	0.45	0.90	360								
39	390		6.3 × 15	0.70	1.40	330							
							10 × 16	0.37	0.74	420			
47	470		8 × 11.5	0.342	0.684	405	▲ 8 × 20	0.37	0.74	420			
68	680		8 × 11.5	0.342	0.684	405	10 × 20	0.30	0.60	490			
82	820						10 × 25	0.25	0.50	540			
100	101		10 × 12.5	0.256	0.512	540	12.5 × 20	0.18	0.36	580			
		▲ 8 × 15	0.230	0.460	535								
120	121		10 × 16	0.194	0.388	600							
150	151		10 × 16	0.194	0.388	660	12.5 × 25	0.13	0.26	710			
180	181		10 × 20	0.147	0.294	890	12.5 × 31.5	0.12	0.24	790			
		▲ 12.5 × 15	0.150	0.300	1020	▲ 16 × 20	0.13	0.26	750				
220	221		10 × 20	0.147	0.294	885	16 × 25	0.10	0.20	890			
		▲ 10 × 25	0.130	0.260	1050	▲ 18 × 20	0.11	0.22	850				
270	271		16 × 15	0.090	0.180	1410							
330	331		12.5 × 20	0.085	0.170	1290	16 × 25	0.090	0.18	1080			
390	391		12.5 × 25	0.070	0.140	1720	18 × 25	0.083	0.166	1260			
		▲ 18 × 15	0.086	0.172	1690								
470	471		12.5 × 25	0.070	0.140	1720	16 × 31.5	0.076	0.152	1310			
		▲ 12.5 × 31.5	0.055	0.110	2090								
560	561		* 16 × 20	0.059	0.118	1770							
680	681		16 × 25	0.050	0.100	2160	18 × 31.5	0.068	0.136	1370			
		▲ 12.5 × 35.5	0.047	0.094	2270	16 × 35.5					0.064	0.128	1410
		* 18 × 20	0.055	0.110	2290								
820	821		16 × 31.5	0.043	0.086	2670							
		▲ 18 × 25	0.043	0.086	2590								
1000	102		16 × 31.5	0.043	0.086	2770	18 × 40	0.047	0.094	1520			
		▲ 16 × 35.5	0.036	0.072	2770								
1200	122		18 × 31.5	0.032	0.064	2950							
1500	152		18 × 35.5	0.030	0.060	3100							
2200	222		18 × 40	0.028	0.056	3200							

▲ : In this case, [6] will be put at 12th digit of type numbering system.

* : In this case, [3] will be put at 12th digit of type numbering system.

V(Code)		160		200		250		315		350		400		450	
Cap. (μF)	Code	2C		2D		2E		2F		2V		2G		2W	
		0.47	R47	6.3 × 11	12	6.3 × 11	12	6.3 × 11	12	8 × 11.5	11	8 × 11.5	11		
1	010	6.3 × 11	17	6.3 × 11	17	6.3 × 11	17	8 × 11.5	16	10 × 12.5	17	10 × 12.5	16	10 × 12.5	18
2.2	2R2	6.3 × 11	25	6.3 × 11	25	8 × 11.5	29	10 × 12.5	28	10 × 16	31	10 × 16	27	10 × 20	29
3.3	3R3	8 × 11.5	36	8 × 11.5	36	10 × 12.5	42	10 × 12.5	34	10 × 16	38	10 × 20	36	12.5 × 20	41
4.7	4R7	8 × 11.5	43	10 × 12.5	50	10 × 12.5	50	10 × 16	45	10 × 20	49	10 × 20	43	12.5 × 20	49
10	100	10 × 12.5	70	10 × 16	80	10 × 20	88	10 × 20	72	12.5 × 20	82	12.5 × 25	72	16 × 25	75
22	220	10 × 20	130	10 × 20	140	12.5 × 25	155	12.5 × 25	120	16 × 25	130	16 × 25	110	16 × 31.5	115
		12.5 × 20	180	12.5 × 25	190	12.5 × 25	190	16 × 25	155	16 × 31.5	160	16 × 31.5	140	● 18 × 35.5	145
33	330	12.5 × 25	220	12.5 × 25	220	16 × 25	230	16 × 35.5	190	● 18 × 35.5	200	● 18 × 35.5	170	20 × 40	175
47	470	12.5 × 25	220	12.5 × 25	220	16 × 25	230	16 × 35.5	190	● 18 × 35.5	200	● 18 × 35.5	170	20 × 40	175
100	101	16 × 25	330	16 × 31.5	335	● 18 × 35.5	340	Δ 18 × 40	285	20 × 40	290	22 × 50	350	25 × 50	350
220	221	● 18 × 35.5	500	Δ 18 × 40	515	20 × 40	525	22 × 50	540	25 × 50	550				
330	331	20 × 40	900	22 × 40	1100	22 × 50	1150								
470	471	22 × 50	1200	22 × 50	1310	25 × 50	1350								

※ Rated ripple current (mArms) at 105°C 120Hz
 Size φ20 × 31 is available for capacitors marked " ● "
 Size φ20 × 35 is available for capacitors marked " Δ "
 In this case, [6] will be put at 12th digit of type numbering system.