



## SPECIFICATIONS

Current Rating: 1A AC,DC

Voltage Rating: 100V AC,DC

Temperature Range:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

Contact Resistance:  $20\text{m}\Omega$  Max.

Insulation Resistance:  $1000\text{M}\Omega$  Min.

Withstanding Voltage: 800V AC/minute

Material: Nylon 66,UL94V-0

## Ordering Information & Dimensions

| PART NO. | Dimensions |       |
|----------|------------|-------|
|          | A          | B     |
| CT-02F   | 2.00       | 6.00  |
| CT-03F   | 4.00       | 8.00  |
| CT-04F   | 6.00       | 10.00 |
| CT-05F   | 8.00       | 12.00 |
| CT-06F   | 10.00      | 14.00 |
| CT-07F   | 12.00      | 16.00 |
| CT-08F   | 14.00      | 18.00 |
| CT-09F   | 16.00      | 20.00 |
| CT-10F   | 18.00      | 22.00 |
| CT-11F   | 20.00      | 24.00 |
| CT-12F   | 22.00      | 26.00 |
| CT-13F   | 24.00      | 28.00 |
| CT-14F   | 26.00      | 30.00 |
| CT-15F   | 28.00      | 32.00 |

DESCRIPTION: 2.00mm PITCH  
HOUSING

TOLERANCES ARE

.X $\pm$ 0.2  
.XX $\pm$   
.XXX $\pm$   
AWG