

Cable Glands




- Material: Brass with nickel plated
- Clamp piece: PA
- Seal piece: NBR & EPDM
- Protection class to: IP68 (tighten part)
- Temperature range: -40°C to 100°C, short time to 120°C

PG series Metric type screw thread cable glands

Thread	∅mm	GL mm	H mm	∅mm	AG mm	Order NO.
PG7	3-6.5	10	19	14	12.5	T.P071006
PG7	2-5	10	19	14	12.5	T.P071005
PG9	4-8	10	20	17	15.2	T.P091008
PG9	2-6	10	20	17	15.2	T.P091006
PG11	5-10	10	21	20	18.6	T.P111010
PG11	3-7	10	21	20	18.6	T.P111007
PG13.5	6-12	10	22	22	20.4	T.P131012
PG13.5	5-9	10	22	22	20.4	T.P131009
PG16	10-14	10	23	24	22.5	T.P161014
PG16	7-12	10	23	24	22.5	T.P161012
PG21	13-18	12	25	30	28.3	T.P211218
PG21	9-16	12	25	30	28.3	T.P211216
PG29	18-25	12	29	40	37	T.P291225
PG29	13-20	12	29	40	37	T.P291220
PG36	22-32	15	35	50	47	T.P361532
PG36	20-26	15	35	50	47	T.P361526
PG42	32-38	15	37	57	54	T.P421538
PG42	25-31	15	37	57	54	T.P421531
PG48	37-44	15	38	64	59.3	T.P481544
PG48	29-35	15	38	64	59.3	T.P481535

Dimension



- Material: Brass with nickel plated
- Clamp piece: PA
- Seal piece: NBR & EPDM
- Protection class to: IP68 (tighten part)
- Temperature range: -40°C to 100°C, short time to 120°C

PG series metal cable glands - breakproof

Thread	∅mm	GL mm	H mm	h mm	∅mm	AG mm	Order NO.
PG7	3-6.5	5	55	6.8	14	12.5	T.P070506F
PG7	2-5	5	55	6.8	14	12.5	T.P070505F
PG9	4-8	6	66	8.2	17	15.2	T.P090608F
PG9	2-6	6	66	8.2	17	15.2	T.P090606F
PG11	5-10	6	77	10.3	20	18.6	T.P110610F
PG11	3-7	6	77	10.3	20	18.6	T.P110607F
PG13.5	6-12	6.5	88	12.3	22	20.4	T.P130712F
PG13.5	5-9	6.5	88	12.3	22	20.4	T.P130709F
PG16	10-14	6.5	98	14.3	24	22.5	T.P160714F
PG16	7-12	6.5	98	14.3	24	22.5	T.P160712F
PG21	13-18	7	111	18.4	30	28.3	T.P210718F
PG21	9-16	7	111	18.4	30	28.3	T.P210716F

Dimension

