

120X120X25 mm

JA1225-0N Series



- **Motor** : Two-pole shaded pole induction motor
- **Frame** : Aluminum Alloy, Painted black
- **Impeller** : Retardant thermoplastic in black color, rated UL94V-0
- **Speed Range** : $\pm 10\%$
- **Impedance protected**

SPECIFICATIONS

Model	Bearing	Nominal Voltage (V)	Frequency (Hz)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Nominal Current (Amp)	Input Power (Watt)	Noise (dBA)	Weight (g)		
JA1225H1B0N	B	110 - 120	50	60.82	0.162	2250	0.18	18	39.4	325		
JA1225L1B0N			60	68.26	0.167	2500	0.10	15	42.5			
			50	54.09	0.107	2000		10	36.3			
JA1225H1S0N			60	50.92	0.080	1900	0.18	9	35.0			
			50	59.96	0.157	2200		18	39.2			
JA1225L1S0N	S		60	65.49	0.151	2400	0.10	15	41.8			
			50	48.76	0.083	1800		10	33.5			
			60	44.47	0.065	1650		9	30.3			
JA1225H2B0N	B	220 - 240	50	60.82	0.162	2250	0.09	17	39.4			
JA1225L2B0N			60	68.26	0.167	2500	0.05	15	42.5			
			50	54.09	0.107	2000		10	36.3			
JA1225H2S0N			60	50.92	0.080	1900	0.09	9	35.0			
			50	59.96	0.157	2200		17	39.2			
JA1225L2S0N	S		60	65.49	0.151	2400	0.05	15	41.8			
			50	48.76	0.083	1800		10	33.5			
			60	44.47	0.065	1650		9	30.3			

Specifications subject to change without notice

