

120X120X38 mm

JA1238-0 Series



- **Motor** : Two-pole shaded pole induction motor
- **Frame** : Aluminum Alloy, Painted black
- **Impeller** : Retardant thermoplastic in black color, rated UL94V-0
- **Speed Range** : $\pm 10\%$
- **Impedance protected**

SPECIFICATIONS

| Model | Bearing | Nominal Voltage (V) | Frequency (Hz) | Air Flow (CFM) | Static Pressure (inchH ₂ O) | Speed (R.P.M.) | nominal Current (Amp) | Input Power (Watt) | Noise (dBA) | Weight (g) | |
|------------|-----------|---------------------|----------------|----------------|--|----------------|-----------------------|--------------------|-------------|------------|----|
| JA1238H1B0 | Dual ball | 110-120 | 50 | 84.0 | 0.277 | 2600 | 0.27 | 23 | 44 | 520 | |
| JA1238M1B0 | | | 60 | 95.0 | 0.316 | 3000 | | 21 | 50 | | |
| JA1238H1S0 | Sleeve | | 50 | 76.0 | 0.215 | 2400 | 0.20 | 14 | 42 | | |
| | | | 60 | 84.0 | 0.179 | 2700 | | 13 | 45 | | |
| JA1238M1S0 | Sleeve | | 50 | 84.0 | 0.277 | 2600 | 0.27 | 23 | 44 | | |
| | | | 60 | 95.0 | 0.316 | 3000 | | 21 | 50 | | |
| JA1238M2B0 | Dual ball | | 220-230 | 50 | 76.0 | 0.215 | 2400 | 0.20 | 14 | | 42 |
| | | | | 60 | 84.0 | 0.179 | 2700 | | 13 | | 45 |
| JA1238H2B0 | Dual ball | | | 50 | 81.0 | 0.277 | 2600 | 0.13 | 20 | | 44 |
| | | | | 60 | 95.0 | 0.316 | 3000 | | 17 | | 50 |
| JA1238M2S0 | Sleeve | 50 | | 76.0 | 0.215 | 2400 | 0.12 | 14 | 42 | | |
| | | 60 | | 84.0 | 0.179 | 2700 | | 13 | 45 | | |

Specifications subject to change without notice

