



Model:	LP103450		Overcharge Detection Voltage(V) 过充保护电压(V)	4.28±0.05
Battery pack specification (电池组规格)	Min.Capacity 最低容量(mAh) (0.2C,25±3°C) ※Single cell capacity (单体电芯容量)	1750	Overdischarge Detection Voltage(V) 过放保护电压(V)	3.0±0.1
	Typical Capacity 典型容量(mAh) (0.2C,25±3°C) ※Single cell capacity (单体电芯容量)	1850	Limited to Max loading current 仅用于最大的负载电流 peak value (A) constant (A) 峰值 3 (A) 持续 1 (A)	
	Nominal Voltage 标称电压(V)	3.7	Customer required Max loading current 客户要求最大的负载电流 peak value (A) constant (A) 峰值 2.5 (A) 持续 1.0 (A)	
	Internal impedance 内阻(≦) (mΩ,AC 1KHZ)	200		
Ambient Conditions (环境温度)	Charge Temp.充电温度(°C)	0~45	If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如果实际应用的负载电流大于EEMB提供值,请提出来,实际的应用情况对PCM的设计至关重要)	
	Discharge Temp.放电温度(°C)	-20~60		
	Humidity(湿度)	65±20%		

Battery protection Related Value:
(相关的电池保护值)

	Drawn:	Hexin	Revise No.:	E4-2009
	Checked 1:	Rachel	Projection:	
	Checked 2:		Page:	1/1
	Approved:		Scale:	1:1
Title	LP103450-PCM-LD		Draw Date:	2014/12/29
File NO.	A10729		Unit:	mm

Remark(备注):
 1. No scratch, distortion, discoloration and leakage on the appearance of the cell (电池表面无划痕、变形、污点及漏液等现象).
 2. RoHS compliant (严格按照ROHS要求生产).